

BEADLESS LITE FLUSH DOOR

Resulting from a dedication to artistic craftsmanship, state-of-the-art technology, and a passion for innovation, Eggers' beadless lite flush door offers clean lines, a streamlined design and a modern touch to any project.



Eggers Industries



ENGINEERING SPECIFICATIONS		BEADLESS LITE FLUSH DOOR	
	20-Minute Single	20-Minute Pairs	Non-Rated
Max. Size	4' x 10'	8' x 10' parallel and dbl. egress	4' x 10' (per leaf)
Thickness	1-3/4" - 2-1/4"		
Core	Particleboard, UF-free particleboard, FSC® certified particleboard, Stave, FSC certified stave, or structural composite lumber (SCL)		
Stiles	Veneered structural composite lumber, solid lumber edges available upon request		
Rails	No-Rail construction is standard for SCL; 1-1/8" for all other core types (multiple-ply optional)		
Reinforcements	Not required for extra heavy duty applications for SCL and stave core		
Faces	All available domestic and foreign veneers, medium density overlay (MDO) and vinyl		
Crossbands	1/11" high density fiberboard		
Lites	Up to 1296 sq. in. standard, SCL, and stave core available with 2868 sq. in. Maximum 6" top rail; factory glazing required.		Size restricted only by min. margins Maximum 6" top rail; factory glazing required
Latching Hardware	Cylinders, mortised, unit, or card locks; 5" backset and deadbolts available		Most available latching hardware
Hinges	Per NFPA 80 - butts, pocket pivots, continuous hinges, pivots (electrical options available)		
Flushbolts	N/A	Automatic corner or extension bolts up to 36"	Corner or extension bolts up to 48"
Exit Hardware	Rim, surface vertical rod (full or top rod only), and fire exit hardware		
Closers, Stops, Holders	Listed surface hardware		
Drop Seals	Listed and approved surface, semi-mortised or mortised		
Special Details	Machining for hardware; installation of lites; sketch faces; applied moulding; kickplates; reveals; solid grillwork and divided lites		
Finish	UV-cured, primed, sealer, full sealer, catalyzed polyurethane and opaque varnish		
Warranty	Life of installation - not suitable for exterior installation		
Standards	WDMA I.S. 1A, AWI Section 1300 8th Edition, NFPA 252, UL 10C, NFPA 80		



**Stile & Rail Doors,
Door Frames, Plywood,
Veneered Components**

Two Rivers Division
One Eggers Drive
Two Rivers, WI 54241
Phone: 920.793.1351
Fax: 920.793.2958

www.eggiersindustries.com

Flush

Neenah Division
164 North Lake Street
Neenah, WI 54956
Phone: 920.722.6444
Fax: 920.722.0357

email: sales@eggiersindustries.com

Eggers releases regular product updates. Please visit www.eggiersindustries.com for the most current and accurate technical information. Specification details published online supersede those in print.

The FSC® certification ensures responsible use of forest products. 04-12
Look for FSC certified products.



The mark of responsible forestry

